



# High quality stainless steel products

We produce a wide variety of stainless steel products in different dimensions. Partially developed together with our customers for their market. They are a broad range of applications as aerospace and defense, chemical processing industry, oil and gas, electrical energy, medical, automotive, food equipment and appliance, construction, mining, transportation and electronics. The products are produced under environmental supervision and all our products are manufactured with first quality raw material. All our products have an excellent corrosion and heat resistance.

## Angle bar



3/12 x 20/100 mm

Angle bar	Angle height										
Thickness	20	25	30	40	50	60	65	70	75	80	100
3	X	X	X	X	X						
4		X	X	X	X						
5		X	X	X	X	X	X	X	X		
6		X	X	X	X	X	X	X	X		
7						X	X	X	X	X	
8						X	X	X	X	X	X
9									X	X	X
10									X	X	X
12									X	X	X

Condition: HRAP, Length according customers requirement, standard length 6000 - 6050 mm

Condition: Hot rolled, annealed and pickled

Tolerances: According ASTM A484

Specifications: According ASTM A276, ASTM 484

## Flat bar



3/30 x 10/200 mm

Flat bar	Bar width																
Thickness	10	12	15	20	25	30	40	50	60	70	75	80	100	120	150	180	200
3	x	x	x	X	X	X	X	X	X								
4	x	x	x	X	X	X	X	X	X								
5	x	x	x	X	X	X	X	X	X	X	X	X					
6	x	x	x	X	X	X	X	X	X	X	X	X	X				
7	x	x	x	X	X	X	X	X	X	X	X	X	X				
8	x	x	x	X	X	X	X	X	X	X	X	X	X	X			
9		x	x	X	X	X	X	X	X	X	X	X	X	X			
10		x	x	X	X	X	X	X	X	X	X	X	X	X	X		
12			x	X	X	X	X	X	X	X	X	X	X	X	X	X	
15				X	X	X	X	X	X	X	X	X	X	X	X	X	X
16				X	X	X	X	X	X	X	X	X	X	X	X	X	X
18					X	X	X	X	X	X	X	X	X	X	X	X	X
20					X	X	X	X	X	X	X	X	X	X	X	X	X
25						X	X	X	X	X	X	X					
30							X	X	X	X	X	X					

Condition: Cold drawn, length according customers requirement, standard length 4000 - 6000 mm

Condition: Hot rolled, annealed and pickled, standard length 4000 - 6000 mm

Tolerances: According ASTM A484

Specifications: According ASTM A276, ASTM 484M, EN 10278/DIN 174

Marking: Laser printing as per grade and size



## Square bar



**Size**  
5 - 100 mm (3/16" - 4")

Lenghts: According customers requirement, standard length 3000 - 6000 mm  
Condition: Heat treatment, soft annealed, solution annealed, oil and water quenched/tempered  
Tolerances: h9, h10, h11, k12, k13  
Specifications: According ASTM A276, ASTM 484M, EN 10278/DIN 174  
Remarks: 100 % identified through handheld spectrometer  
Specialities: Grit polished as customers requirement  
Bars end finish: Chamfered, plain ends without burrs or sharp edges

---

## Hexagonal bar



**Size**  
5 - 100 mm (3/16" - 4")

Lenghts: According customers requirement, standard length 3000 - 6000 mm  
Condition: Hot rolled, annealed pickled and cold drawn  
Tolerances: According ASTM A484, h9, h10, h11  
Specifications: According ASTM A276, ASTM 484M, EN 10278/DIN 174  
Remarks: 100 % identified through handheld spectrometer  
Specialities: Grit polished as customers requirement  
Bars end finish: Chamfered, plain ends without burrs or sharp edges  
Marking: Laser printing as per grade and size

---

## Round bar



**Size**  
3 - 508 mm (1/8" - 20")

Grades: Austenitic: 303, 304, 304L, 316, 316L, XM-19  
Ferritic: 416, 416RQ, 416HT, 410, 410QT, 410DQT, 431  
Duplex: 2205, LDX2101  
Martensitic: 17-4, 17-4 DH1150, 17-4 H1075, 17-4 H1050, 15-5  
Nickel alloys: 400, 405, K500, 600, 601, 200, 201, 825, 625, 718, 800, 800HT  
Lenghts: According customers requirement, standard length 3000 - 6000 mm  
Condition: Cold drawn, cold finished, smooth turned, rough turned, hot rolled, centerless ground, turned ground & polished, bearing soft quality, pump shaft  
Processing: Cutting up to 20" (508mm) diameter  
Centerless grinding 1/16" to 11 1/2" diameter  
Turning up to 12" diameter  
Straightening up to 8" diameter  
Chamfering 1/4" to 1 1/2" diameter  
Polishing up to 12" diameter  
Tolerances: According ASTM A484  
Specifications: According ASTM A276, ASTM A484, ASTM A479, ASTM A585 (303 + 416), ASTM A564 (17-4)  
Remarks: Single packaging by plastic bag for grit polished surface products possible

---

## Quality and Logistics

All our products are manufactured according the EU guidelines and correspond according the EN10204-2.2, EN10204-3.1 directives including the CE compliance. We provide a full service to all our customers as DDP shipments directly to their domicile; without any troubles for the transportation, the ordering of containers, customs, port handling fees and so on for our customers.

---